

University of Groningen

Fundamental limitations of THz and Niobiumnitride SIS mixers

Dieleman, Pieter

IMPORTANT NOTE: You are advised to consult the publisher's version (publisher's PDF) if you wish to cite from it. Please check the document version below.

Document Version

Publisher's PDF, also known as Version of record

Publication date:

1998

[Link to publication in University of Groningen/UMCG research database](#)

Citation for published version (APA):

Dieleman, P. (1998). *Fundamental limitations of THz and Niobiumnitride SIS mixers*. [Thesis fully internal (DIV), University of Groningen]. University of Groningen.

Copyright

Other than for strictly personal use, it is not permitted to download or to forward/distribute the text or part of it without the consent of the author(s) and/or copyright holder(s), unless the work is under an open content license (like Creative Commons).

The publication may also be distributed here under the terms of Article 25fa of the Dutch Copyright Act, indicated by the "Taverne" license. More information can be found on the University of Groningen website: <https://www.rug.nl/library/open-access/self-archiving-pure/taverne-amendment>.

Take-down policy

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Downloaded from the University of Groningen/UMCG research database (Pure): <http://www.rug.nl/research/portal>. For technical reasons the number of authors shown on this cover page is limited to 10 maximum.

Fundamental Limitations of THz Niobium and Niobiumnitride SIS Mixers

Pieter Dieleman

The cover picture is taken the morning after the 1953 flood disaster in the province of Zeeland, the Netherlands. Clearly visible are the holes in the sea dike through which the water flows with great force. Apart from the devastating effects, the apparent huge stream of water through these holes provides an expressive analogue to the effects of pinholes in tunnel barriers as described in this thesis. (Copied with permission from "De watersnood in Zeeuws-Vlaanderen", by G. Sponslee and E. Steyns, van Geyt productions, Hulst, the Netherlands).

The reading committee for this thesis consists of Prof.Dr.Ir. J.E. Mooij, Prof.Dr. M.J. Feldman, and Prof.Dr. K.H. Gundlach.

This thesis is typeset in Times Roman with L^AT_EX.

This work was performed at the Department of Applied Physics of the University of Groningen and the Space Research Organization of the Netherlands (SRON) as part of the research program of the *Stichting voor de Technische Wetenschappen* (STW), with financial support from the *Nederlandse Organisatie voor Wetenschappelijk Onderzoek*. This work is also supported by the *European Space Agency* (ESA) under contract no: 7898/88/NL/PB(SC) and 11653/95/NL/PB.

————— Rijksuniversiteit Groningen —————

Fundamental Limitations
of THz Niobium
and Niobiumnitride
SIS Mixers

————— Proefschrift —————

ter verkrijging van het doctoraat in de
Wiskunde en Natuurwetenschappen
aan de Rijksuniversiteit Groningen
op gezag van de
Rector Magnificus Dr. F. van der Woude
in het openbaar te verdedigen op
vrijdag 24 april 1998
des namiddags te 1.15 uur.

door

————— Pieter Dieleman —————

geboren op 24 mei 1970
te Kommerzijl.

Promotor: Prof. Dr. Ir. T.M. Klapwijk
Referent: Dr. M.W.M. de Graauw

Preface

This thesis describes the use of superconducting niobium and niobiumnitride tunnel junctions as heterodyne mixing elements in the submillimeter frequency range from 600 to 1000 GHz. In this frequency range Nb as well as NbN layers exhibit significant absorption of submillimeter radiation, making them unsuitable as impedance matching embedding structures. This brings about the inclusion of normal metals in the design of these detectors. The frequency range obtainable with these "hybrid" detectors as well as the attainable ultimate sensitivity are the main topics of this thesis.

Ch. 1 is an introduction to the work presented in the thesis, and describes the historical development and the basic principles of operation of heterodyne receivers based on superconducting tunnel junctions. The fabrication, materials properties and their effect on the electrical characteristics of Nb and NbN tunnel junctions are discussed in Ch. 2 as well as the fabrication related RF radiation losses in superconductors and normal metals.

The operation of the receiver as a whole and the junction in particular will be illustrated in Ch. 3 by means of a "case study" of a Nb junction with aluminum circuitry. Measured data are compared in detail with the quantum theory of mixing.

An interesting observation when employing aluminum embedding is an improved transport of the heat generated by Joule heating of the device when operated as a detector. The cooling efficiency of aluminum *vs.* niobium embedding of the junction is investigated in Ch. 4. Using the simulation developed in Ch. 3 the effect of this enhanced heat transport is on the mixing properties is investigated.

Ch. 5 deals with the feasibility of NbN junctions in the frequency range of 600 to 1000 GHz, in which an analysis method is employed similar to that in Ch. 3. The NbN junctions exhibit a significantly enhanced shot noise which dominates the performance of the device. The physical mechanism behind this is described in Ch. 6. The same noise enhancement mechanism is found to be present in high

critical current density Nb junctions as well. This observation, described in Ch. 7 answers a long-standing question on the discrepancy between the noise measured and theoretically expected.

Appendix A discusses the lay-out of the used waveguide mixers and the experimental methods used to determine the physical properties of the devices.

A summary of the work performed and the implications of the results for the feasibility of superconducting tunnel junctions in the THz regime is given in Ch. 8. The thesis ends with a summary both in English and Dutch.

Contents

1	Submm radiation detection	1
1.1	Understanding the universe	1
1.2	Atmospheric research	2
1.3	Radiation detection at THz frequencies	3
1.3.1	Detector requirements	3
1.3.2	Coupling of radiation to the detector	4
1.3.3	Submm radiation detection modes	6
1.4	Heterodyne detectors	9
1.4.1	Schottky-barrier diode	9
1.4.2	SIS junctions	9
1.4.3	HEB junctions	10
1.5	SIS heterodyne detectors	11
1.6	Frequency range of SIS operation	13
1.6.1	Tuning circuit characteristics	13
1.6.2	Junction frequency range limitations	14
1.7	Conclusions	15
2	Materials aspects and SIS characteristics	17
2.1	Fabrication of SIS mixer structures	17
2.1.1	Nb tunnel junction fabrication	19
2.1.2	NbN tunnel junction fabrication	20
2.2	I - V characteristics vs. barrier structure	27
2.2.1	Aluminum oxide growth	27
2.2.2	Dependence of electrical properties on J_c	28
2.2.3	Current transport in pinholes	33
2.3	Influence of MAR on THz radiation mixing	36
2.3.1	Effect of microwave radiation on MAR	36

2.3.2	Radiation modifies MAR modifies mixing properties . . .	37
2.4	Integrated tuning structures	38
2.4.1	Transmission line operation	38
2.4.2	Low-loss radiation coupling	41
2.5	Surface resistance of metals and superconductors	42
2.5.1	Nb surface impedance	44
2.5.2	Al surface impedance	44
2.5.3	NbN surface impedance	45
2.6	Conclusions	46
3	Performance analysis of Nb junctions at 800–1000 GHz	51
3.1	Introduction	51
3.2	Receiver configuration	52
3.3	Heterodyne measurements	53
3.4	Receiver noise analysis	55
3.4.1	RF components	56
3.4.2	Mixer characteristics	56
3.5	Discussion and conclusions	58
4	DC heating in SIS junctions	63
4.1	Introduction	63
4.2	Junction layout	64
4.3	Heat flow	64
4.4	Heat relaxation mechanisms	65
4.5	Thermal healing length	66
4.6	Influence on mixer performance	68
4.7	Conclusions	69
5	Performance limitations of NbN SIS junctions	71
5.1	Introduction	72
5.2	Junction characteristics and measurement setup	72
5.3	Shot noise measurements and modeling	73
5.4	Receiver noise measurements	77
5.5	Conclusions	79

6	Observation of Andreev reflection enhanced shot noise	83
6.1	Introduction	84
6.2	Sample layout and characteristics	85
6.3	Shot noise measurement	85
6.4	Shot noise in NbN junctions	87
6.5	Charge cluster calculation	88
6.6	Conclusions	91
7	Shot noise beyond the Tucker theory in niobium tunnel junction mixers.	95
7.1	Introduction	95
7.2	Junction characteristics	96
7.3	Measurement setup	97
7.4	Noise measurements	99
7.5	Shot noise calculation	99
7.6	Implications for the noise temperature	99
7.7	Effects on the receiver characteristics	101
7.8	Conclusions	101
8	Summary and discussion	105
8.1	Integrated tuning structures	105
8.2	Nb junction results	106
8.3	NbN junction results	107
8.4	Future development of THz detectors	108
A	Performing heterodyne measurements	111
A.1	Junction performance testing	111
A.2	Receiver layout	113
	Samenvatting	115
	Dankwoord	121
	List of publications	123

